

# LITTLE DAVID<sup>®</sup>

## Automatic Print and Apply Label Application System

The Little David<sup>®</sup> LS-800 is designed specifically for integration into automatic print/apply labeling applications. Labels can be affixed directly to boxes, pallets or products. Multiple mounting strategies are available to afford installation flexibility. The LS-800 is ideal for the printing and applying of labels that require high quality bar code, text and graphic images.

AVAILABLE APPLICATORS



- Microprocessor driven controller w/user-friendly key pad and LCD display for easy access to label application parameters
- User-friendly label format software available for label design, alpha numeric and bar code printing
- 74 save areas for quick recall of label placement settings
- Variable 12"/second maximum label printing speed (based on printer selection)
- Non-cantilevered double frame design that eliminates web drift
- Simple threading path ensures quick label change
  - Right or left handed dispensing available
  - Balanced feed assures consistent label tension and reduces web breakage
- Next label out feature for true 1 to 1 application
- Built in USA

# LS-800

## Standard Features:

- Labeling head
- Applicator
- Proximity product sensor
- Photoelectric label sensor
- 30-inch crosstube mount
- Microprocessor

## Specifications:

### Machine Dimensions

Length: 34-11/32" (872 mm)

Width: 30" (762 mm)

Height: 40-3/4" (1035 mm)

Weight: 165 lbs (74 kg)

### Label Dimensions

Width: 1" – 5-1/4" (25.4 mm – 133.35 mm)

Length: 1/2" – 14" (12.7 mm – 355.6 mm)

### Label Roll Requirements

Finish: Pressure sensitive die cut  
with 1/8" (3.17mm) gap

Outside Diameter: 11-7/8" (301.6 mm)

15-7/8" (403.2 mm) optional

Core Diameter: 3" (76.2 mm)

4" (101.6 mm) optional

### Electric

115 – 230 Volt, 50/60 Cycle, 5 Amps

### Air

40 – 60 PSI at .5 CFM while dispensing

**LOVESHAW** **LOVESHAW Europe**  
an **ITW** Company A Division of ITW Ltd.

LITTLE DAVID PRODUCTS DIVISION  
Route 296 Box 83  
South Canaan, PA 18459  
(570) 937.4921 Fax (570) 937.3229  
1(800) 581.7119

Unit 9 Brunel Gate,  
West Portway Industrial Estate  
Andover, Hampshire England SP 10 3 SL  
Tel: (1264) 357511 Fax: (1264) 355964

visit  
[www.loveshaw.com](http://www.loveshaw.com)



"H" floor mounting stand  
with casters and lift off  
screws

## Printer/Applicator Data:

**Printing Label Speed:** Up to 12"/second (305mm)  
based on printer selection

**Accuracy:** +/- 1/32" (+/- .79 mm)

**Product Sensing:** Photoelectric

**Label Sensing:** Photoelectric

**Print Resolution:** 203 dpi (8 dots/mm) (305 dpi available)

**Printing Method:** Thermal transfer printer  
(direct thermal available)

**Standard Printer:** Sato M-8485Se (optional printers available)

**Communication Interface:** RS232C

**Bar Code Symbology:** UPC-A, UPC-F, EAN-8, Code 39,  
Code 128, Interleaved 2/5, UCC/EAN 128, Postnet,  
2D, and many others.

## Available Applicators Include:

Tamp, Blow On, Tamp/Blow, Touch'n'Go,  
Dual Tamp/Corner Wrap, Pallet Applicator,  
Front Panel Swing Arm

## Available Options:

- 305 dpi print resolution
- "H" floor mounting stand, vertical delta mount
- Direct thermal
- Low media and media out signal alarm beacon
- Printer selection (Sato, Zebra, Datamax)
- Label generation software available
- Left-hand feed printer
- Parallel (IEEE1284) and Ethernet-10/100BaseT  
communication interfaces
- Various product sensors

