

LITTLE DAVID®



LOVESHAW an ITW Company

Quality Engineered

Random Legend Case Sealer

The Little David® Random Legend is now the industry standard. When you are looking for a truly superior engineered random, look no further than the Little David Random Legend.

One look at all the standard features and you will see why Little David random Legend is leading the way in innovation.

These are what
make Legends:

- Light touch “live” roller table for centering
- Built-in adjustable “burp” for head, allowing easy box exiting
- Interchangeable Tape Cartridges
- Light touch head paddle for head raising
- Patented leg extensions
- Patent pending safe mast system
- Top cartridge tips back for easy tape change over
- Patented mast trolley system enclosed for safety



www.loveshaw.com

Random Legend

Safe —

- Patented single mast design allows clear access to all components

Fast Operation —

- Back to back feature allows for high speed case sealing
- Head burps automatically for easy case release

Quality Engineered —

- Quality GE motor & Boston gear reducer

Flexible —

- Interchangeable CaseLocker® ST top and bottom tape cartridge.
- Lockable head height & side rail allows for uniform mode

Easy Operation —

- Self-tensioning & self-centering belts
- Light touch live roller table for centering
- Head raising switch for easy bottom tape changeover

Patented leg extensions are clearly marked with graduated scales in both inches and metric dimensions. Leg adjustments slide and lock in place to accommodate conveyor heights from 22.25 in. to 32.25 in. (565 mm to 819 mm)

Features:

Flexible —


- Tapes boxes from 3" (76 mm) to 24" (610 mm)
- Converts from 2" to 3" wide tape

Easy Operation —

- Plug in operation
- Minimal operator training required
- Sealed drive system
- CaseLocker® ST tape cartridge requires no lubrication
- Front roller pack table

Safe —

- UL listed
- Patented single mast design allows clear access
- Knife guard system of the CaseLocker® ST tape cartridge allows the blade to be exposed only when the rollers are depressed



Specifications:

Power Requirements:

115 – 220 volts, single phase, 60 cycle
(other voltage available, consult Loveshaw)

Air Requirements:

10 SCFM @ 70 PSI

Operating Speed:

Continuous belt drive; 80'/minute (24.4 m/min.)
(production rate depends on box size & operator dexterity)

Weight:

275 lbs (125 kg) uncrated

Case Capacity: (with 2" wide Caselocker® ST Cartridge)

Min: Height 3" (76 mm), Width 4-1/2" (114 mm),
Length 4- 1/2" (114 mm)

Max: Height 24" (610 mm)*, Width 22" (559 mm), Length infinite
*Conveyor height minimum is 22-1/4" (565mm)

Reliable Performance — Warranty

- 1 Year all components
- 2 Years Gear Reducer
- 3 Years Cartridge*

*Moving and wear parts are not included. Other restrictions may apply. Consult Loveshaw or your authorized Little David® Distributor for details

Options:

- Casters
- Leg adjustments to accommodate various conveyor heights
- High mast for box heights to 34" (864 mm)
- Rear standard or roller pack table

LOVESHAW **LOVESHAW Europe**
an **ITW** Company A Division of ITW Ltd.

LITTLE DAVID PRODUCTS DIVISION
Route 296 Box 83
South Canaan, PA 18459
(570) 937.4921 Fax (570) 937.3229
1(800) 581.7119

Unit 9 Brunel Gate,
West Portway Industrial Estate
Andover, Hampshire England SP 10 3 SL
Tel: (1264) 357511 Fax: (1264) 355964

visit
www.loveshaw.com

